

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

1/4




FIG. 1  
(Prior Art)




FIG. 2

2/4




FIG. 3




FIG. 4

3/4




FIG. 5




FIG. 6




FIG. 7

4/4




FIG. 8

Adding Hydroxyl to the combustion flow stream at least one point upstream or at the catalytic converter for treating exhaust gases produced by a combustion engine to at least reduce one pollutant from incomplete Combustion and/or oxides of nitrogen

Treating the exhaust gases with a high surface receptacle such as a catalytic converter

FIG. 9